



Proof, Photo & Production media PRODUCT DATASHEET



EFI Production Premium Paper 1200XF Semiglossy



This PE microporous coated paper has a very high resolution, is suitable for both hot and cold lamination and distinguishes itself by the universal suitability for dye and pigmented inks and the very wide colour gamut.



Description:

Semiglossy paper
PE microporous coated
Very wide colour gamut
Suitable for hot and cold laminating

Application:

Production applications
Presentations
Posters

Technical data:

Weight	200	g/m ²
Thickness	200	μ
Opacity	94	%
Gloss [Tappi 75°]	55	%
L*a*b* Paper white	95,46 / -0,25 / -3,40	
Storage	15 - 30 °C (40 - 60% RH)	

Size

Sheet	Roll	Core	Roll	Core
DIN A4 (210 x 297 mm)	32,9 cm x 30 m (13")	3"*	106,7 cm x 30 m (42")	3"*
DIN A3 (297 x 420 mm)	36,0 cm x 30 m (14,17")	3"*	111,8 cm x 30 m (44")	3"*
DIN A3+ (330 x 483 mm)	43,2 cm x 30 m (17")	3"*	127,0 cm x 30 m (50")	3"*
DIN A2 (420 x 594 mm)	61,0 cm x 30 m (24")	3"*	137,0 cm x 30 m (54")	3"*
DIN A2+ (480 x 628 mm)	91,4 cm x 30 m (36")	3"*	152,4 cm x 30 m (60")	3"*
DIN A1 (594 x 841 mm)			162,6 cm x 30 m (64")	3"*
DIN A1+ (625 x 914 mm)				
DIN A0 (841 x 1189 mm)				
DIN A0++ (914 x 1250 mm)				

*) supplied with each two adapters 3" to 2" core