



Proof, Photo & Production media

PRODUCT DATASHEET



EFI Production ecoS Backlit BLG150 Glossy



This printing substrate is a high glossy polyester film for spot and transmitted light applications. As this backlit is water and scratch resistance it is very suitable for outdoor applications even without lamination.

Description:

Glossy polyester film
High color brilliance for day and night applications
Water resistant
Scratch resistant
Outdoor durability up to 2 years without laminating

Application:

Photorealistic prints
Indoor and outdoor applications
Areas with a high humidity
Suitable for Eco-Solvent, Mild-Solvent and True-Solvent printers, so as with latex and also UV printers

Technical data:

Weight	180	g/m ²
Thickness	150	μ
Opacity	43	%
Gloss [Tappi 75°]	5	%
L*a*b* Paper white	90 / -0,4 / -0,2	
Storage	15 - 30 °C (40 - 60% RH)	

Size

Roll	Core
61,0 cm x 20 m (24")	3"*)
76,2 cm x 30 m (30")	3"*)
91,4 cm x 20 m (36")	3"*)
106,7 cm x 20 m (42")	3"*)
127,0 cm x 20 m (50")	3"*)
137,0 cm x 20 m (54")	3"*)
152,0 cm x 20 m (60")	3"*)
162,6 cm x 20 m (64")	3"*)

*) supplied with each two adapters 3" to 2" core