

Product data sheet

EFI CertProof Paper 6225XF Semimatt

The EFI CertProof Paper 6225XF Semimatt is a universal PE-coated, microporous paper designed for offset and gravure proofing. It shows outstanding results with the latest ink generation of the leading printer manufacturers (K3, Lucia, Vivid, Vivera, etc.). With its very wide color gamut the media is capable of Spot-Color Proofing and meets the industry's most stringent quality and consistency requirements. The huge gamut covers paper type classes PT1, PT2 and PT3. The EFI CertProof Paper 6225XF has almost no optical brighteners which minimises metamerism and reduces measurement errors in the profiling process. It is supplied with the EFI-FOGRA print on the backside. Naturally this media is compatible for Fogra proof creation according to ISO 12647-7.

Description:

- Semimatt coated paper
- Wide color gamut
- Very low content of optical brighteners
- Fast drying (Instant-dry)
- Universal use



Application:

- Proofing
- Photo

Technical data:

- Weight	225	g / m ²
- Thickness	260	μ
- Opacity	96	%
- Storage	15 - 30	°C (40 - 60% RH)
- L*a*b*	96,0 / 0,0 / -1,8	

Sizes

Sheets		Rolls		Core	Rolls		Core
DIN A4	(210 x 297 mm)	25,4 cm x 30 m	(10'')	3'' *	106,7 cm x 30 m	(42'')	3'' *
SUPER A4	(241 x 340 mm)	32,9 cm x 10 m	(13'')	2''	111,8 cm x 30 m	(44'')	3'' *
DIN A3	(297 x 420 mm)	32,9 cm x 30 m	(13'')	3'' *	127,0 cm x 30 m	(50'')	3'' *
DIN A3+	(330 x 483 mm)	36,0 cm x 30 m	(14,17'')	3'' *	135,0 cm x 30 m	(53,125'')	3'' *
A3++	(329 x 558 mm)	43,2 cm x 30 m	(17'')	3'' *	137,0 cm x 30 m	(54'')	3'' *
DIN A2	(420 x 594 mm)	45,7 cm x 25 m	(18'')	2'' ***)	152,4 cm x 30 m	(60'')	3'' *
DIN A1	(594 x 841 mm)	50,8 cm x 30 m	(20'')	3'' *			
		61,0 cm x 25 m	(24'')	2'' **)			
		61,0 cm x 30 m	(24'')	3'' *			
		91,4 cm x 30 m	(36'')	3'' *			