



**PRODUCT DATASHEET**  
**CPGWF/II**



**Description:**

High resolution  
Semimatt coated  
Universal use  
Very fast drying  
Suitable for both hot and cold laminating  
High color fidelity, Brilliance <54%  
Wipe fast\*

**Ideal for:**

Posters  
Displays  
Billboards  
Photorealistic prints

**Technical data:**

Weight 150 g/m<sup>2</sup>  
Thickness 170 μ  
Opacity 85 %  
Storage 10-30 °C (40-60% RH)

**Sizes**

Sheets		Rolls	Core	Rolls	Core
DIN A4	(210 x 297 mm)	43,2 cm x 30 m (17")	3"*)	127,0 cm x 30 m (50")	2"
DIN A3	(297 x 420 mm)	45,7 cm x 30 m (18")	2"	132,0 cm x 30 m (52")	2"
DIN A3+	(330 x 483 mm)	61,0 cm x 30 m (24")	2"	135,0 cm x 30 m (53,125")	3"*)
DIN A2	(420 x 594 mm)	91,4 cm x 30 m (36")	2"	137,2 cm x 30 m (54")	2"
		91,4 cm x 30 m (36")	3"*)	137,2 cm x 30 m (54")	3"*)
		106,7 cm x 30 m (42")	2"	152,4 cm x 30 m (60")	2"
		111,8 cm x 30 m (44")	2"		*) supplied with each two adapters 3" to 2" core

\* The wipe fastness of this product in combination with oil based inks is limited. Independent from ambient temperature drying time may be very long. RECOMMENDED ONLY FOR INDOOR APPLICATIONS.

**INKJET PAPER**

**Important:** Before using our print media, please verify that it is suitable for use with your printer. We shall not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks or printers. Specifications are subject to change without notice. This Product Data Sheet is intended to be used as a guideline only.

**Storing conditions:** Please keep product in the supplied boxes for best possible protection. Product must be stored in a cool and dry environment, exposure to sun light is to be avoided.



**Tecco GmbH**  
Buchholzstraße 79 - 51469 Bergisch Gladbach - Germany  
Phone: +49-(0)2202-2924-0 - Fax: +49-(0)2202-2924-99  
e-Mail: contact@tecco.de - www.tecco.de