



PRODUCT DATASHEET
CPGWF/II 'Heavy'



Description:

High resolution
 Semimatt coated
 Universal use
 Very fast drying
 Suitable for both hot and cold laminating
 High color fidelity, Brilliance <54%
 Wipe fast*

Ideal for:

Posters
 Displays
 Billboards
 Photorealistic prints

Technical data:

Weight 180 g/m²
 Thickness 200 μ
 Opacity 94 %
 Storage 10-30 °C (40-60% RH)

Sizes

Sheets		Rolls	Core	Rolls	Core
DIN A4	(210 x 297 mm)	43,2 cm x 30 m (17")	3" *	127,0 cm x 30 m (50")	3" *
DIN A3	(297 x 420 mm)	61,0 cm x 30 m (24")	3" *	137,2 cm x 30 m (54")	3" *
DIN A3+	(330 x 483 mm)	91,4 cm x 30 m (36")	3" *	152,4 cm x 30 m (60")	3" *
DIN A2	(420 x 594 mm)	106,7 cm x 30 m (42")	3" *	162,6 cm x 30 m (64")	3" *
		111,8 cm x 30 m (44")	3" *		

*) supplied with each two adapters 3" to 2" core

* The wipe fastness of this product in combination with oil based inks is limited. Independent from ambient temperature drying time may be very long. RECOMMENDED ONLY FOR INDOOR APPLICATIONS.

INKJET PAPER

Important: Before using our print media, please verify that it is suitable for use with your printer. We shall not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks or printers. Specifications are subject to change without notice. This Product Data Sheet is intended to be used as a guideline only.

Storing conditions: Please keep product in the supplied boxes for best possible protection. Product must be stored in a cool and dry environment, exposure to sun light is to be avoided.